



Product Introduction

Product Name:	Current Probe PT710-A
Short Description:	300KHZ 0.05A-200A ±3%:50mA~10A peak at 100mV/A ±4%:400mA~40A peak at 10mV/A ±15%:40A~100A peak

MODEL	PT710-A
Feature	100KHz, ≥10mA, Low noise type
Max. DC AC Current	±100A DC
Max. DC AC Peak	200A P-P
Max. DC AC RMS	70A RMS
Range Selection Division	2 Range 10mV/A; 100mV
Max. Test Wire	≤11Φ
Max. Sensitivity	10mA
Bandwidth (-3dB)	DC~100KHz
Rise time	3.5μs
DC Accuracy (Typical)	±3%:50mA~10A peak at 100mV/A ±4%:400mA~40A peak at 10mV/A ±15%:40A~100A peak
Max. Working voltage	300V CAT III
Max. Floating voltage	600V CAT II



Product Introduction

Product Name:	Current Probe PT710-B
Short Description:	500KHZ 30mA-50A ±3%:30mA~5A peak at 200mV/A ±4%:300mA~20A peak at 20mV/A ±15%:20A~50A peak

ADD: Room A413 Area 2 TCL cultural industrial park, No.69 Guangpu west road, Guangzhou, China
Tel: +86-20-61038868 Fax : +86-20-61038838
E-mail: sales@pintech.com.cn
Website: www.pintech.com.cn